

## **§ 92.10-45**

### **§ 92.10-45 Weather deck communications.**

(a) Vertical communication shall be provided between the various weather decks by means of permanent inclined ladders.

### **§ 92.10-90 Vessels contracted for prior to November 19, 1952.**

(a) Existing arrangements previously approved will be considered satisfactory so long as they are maintained in good condition to the satisfaction of the Officer in Charge, Marine Inspection. Minor repairs and alterations may be made to the same standards as the original design: *Provided*, That in no case will a greater departure from the standards of §§ 92.10-5 through 92.10-45 be permitted than presently exists. Nothing in this paragraph shall be construed as exempting any vessel from having 2 means of escape from all main compartments which are accessible to the passengers, if carried, or where the crew are normally quartered or employed.

## **Subpart 92.15—Ventilation**

### **§ 92.15-1 Application.**

The provisions of this subpart, with the exception of § 92.15-90, shall apply to all vessels contracted for on or after November 19, 1952. Vessels contracted for prior to November 19, 1952, shall meet the requirements of § 92.15-90.

### **§ 92.15-5 Vessels using fuel having a flashpoint of 110 degrees or lower.**

(a) Where liquid fuel having a flashpoint of 110 degrees F. or lower is used for main or auxiliary machinery or for starting purposes, the spaces containing such machinery or fuel tanks shall have ventilation as required by this section.

(1) At least 2 ventilators fitted with cowls or their equivalent for the purpose of properly and effectively ventilating the bilges of every engine and fuel-tank compartment in order to remove any flammable or explosive gases.

(2) Vessels constructed so that the greater portions of the bilges under the engine and fuel tanks are open or exposed to the natural atmosphere at all

## **46 CFR Ch. I (10-1-12 Edition)**

times are not required to be fitted with ventilators.

### **§ 92.15-10 Ventilation for closed spaces.**

(a) Except as noted in paragraph (c) of this section, all enclosed spaces within the vessel shall be properly vented or ventilated. Means shall be provided to close off all vents and ventilators.

(b) Means shall be provided for stopping all fans in ventilation systems serving machinery and cargo spaces and for closing all doorways, ventilators and annular spaces around funnels and other openings to such spaces, from outside these spaces, in case of fire.

(c) On unmanned cargo barges not fitted with a fixed bilge system, vents and ventilators may be omitted from void spaces.

(d) The ventilation of spaces that are “specially suitable for vehicles” shall be in accordance with §§ 97.80-1, 111.105-39 and 111.105-40 of this chapter, as applicable.

(1) Areas below the weather deck shall be provided with continuous pressure-positive ventilation at each level on which vehicles are transported.

(2) The quantity of ventilating air shall be not less than 1 cubic foot per minute per square foot of deck area.

(3) The ventilation system shall be such as to prevent air stratification as well as to prevent the accumulation of air pockets.

(4) An alarm system shall be provided which will indicate the loss of required ventilation. The alarm location shall be in a normally manned space acceptable to the Commandant.

(e) For requirements regarding controls of electrically powered ventilation systems, see subchapter J (Electrical Engineering) of this chapter.

[CGFR 65-50, 30 FR 16983, Dec. 30, 1965, as amended by CGFR 66-33, 31 FR 15284, Dec. 5, 1966; USCG-2003-16630, 73 FR 65193, Oct. 31, 2008]

### **§ 92.15-15 Ventilation for crew quarters and, where provided, passenger spaces.**

(a) All living spaces shall be adequately ventilated in a manner suitable to the purpose of the space.

(b) On vessels of 100 gross tons and over, except for such spaces as are so located that under all ordinary conditions of weather, windows, ports, skylights, etc., and doors to passageways can be kept open, all crew spaces shall be ventilated by a mechanical system, unless it can be shown that a natural system will provide adequate ventilation. However, vessels which trade regularly in the tropics shall, in general, be fitted with a mechanical ventilation system.

**§ 92.15–90 Vessels contracted for prior to November 19, 1952.**

(a) Existing arrangements previously approved will be considered satisfactory so long as they are maintained in good condition to the satisfaction of the Officer in Charge, Marine Inspection. Minor repairs and alterations may be made to the same standards as the original design provided that in no case will a greater departure from the standards of §§ 92.15–5 through 92.15–15 be permitted than presently exists.

**Subpart 92.20—Accommodations for Officers and Crew**

SOURCE: CGD 95–027, 61 FR 26005, May 23, 1996, unless otherwise noted.

**§ 92.20–1 Application.**

(a) The provisions of this subpart apply to all vessels of 100 gross tons and over contracted for on or after November 19, 1952. Vessels of 100 gross tons and over contracted for prior to November 19, 1952 must meet the requirements of § 92.20–90.

(b) Vessels of less than 100 gross tons must meet the applicable requirements of this subpart insofar as is reasonable and practicable.

**§ 92.20–5 Intent.**

It is the intent of this subpart that the accommodations provided for officers and crew on all vessels must be securely constructed, properly lighted, heated, drained, ventilated, equipped, located, arranged, and insulated from undue noise, heat, and odors.

**§ 92.20–10 Location of crew spaces.**

(a) Crew quarters must not be located farther forward in the vessel than a vertical plane located at 5 percent of the vessel's length abaft the forward side of the stem at the designed summer load water line. However, for vessels in other than ocean or coastwise service, this distance need not exceed 8.5 meters (28 feet). For the purposes of this paragraph, the vessel's length must be as defined in § 43.15–1 of subchapter E (Load Lines) of this chapter. Unless approved by the Commandant, no section of the deck head of the crew spaces may be below the deepest load line.

(b) There must be no direct communication, except through solid, close fitted doors, or hatches between crew spaces and chain lockers, or machinery spaces.

**§ 92.20–15 Construction.**

All crew spaces are to be constructed and arranged in a manner suitable to the purpose for which they are intended and so that they can be kept in a clean, workable, and sanitary condition.

**§ 92.20–20 Sleeping accommodations.**

(a) Where practicable, each licensed officer must be provided with a separate stateroom.

(b) Sleeping accommodations for the crew must be divided into rooms, no one of which shall berth more than 4 persons.

(c) Each room must be of such size that there is at least 2.78 square meters (30 square feet) of deck area and a volume of at least 5.8 cubic meters (210 cubic feet) for each person accommodated. The clear head room must be not less than 190 centimeters (75 inches). In measuring sleeping accommodations, any furnishings contained therein for the use of the occupants are not to be deducted from the total volume or from the deck area.

(d) Each person shall have a separate berth and not more than one berth may be placed above another. The berth must be composed of materials not likely to corrode. The overall size of a